

MSDS Material Safety Data Sheet

Ralph Wilson Plastics Company

MSDS Number: 17293
Page 1 of 5

Lokweld 600 Adhesive

Revision Date: 01/30/13
Revision No: 5

1 PRODUCT AND COMPANY IDENTIFICATION

Common Name: Lokweld 600 Adhesive

Manufacturer: RALPH WILSON PLASTICS COMPANY
P. O. BOX 6110 – 2400 WILSON PLACE
TEMPLE, TX 76503
INFORMATION PHONE: 800-433-3222 (USA)

Trade Name: Lokweld 600 Adhesive

Material Uses: Adhesive for laminate

In Case of Emergency Contact CHEMTREC: 800-424-9300 (USA)
703-527-3887 (INTERNATIONAL)

2 HAZARDS IDENTIFICATION

Route of Entry: Skin, eyes, respiratory tract, ingestion.

Target Organs: Lung, liver, kidney, central nervous system (CNS), and peripheral nervous system.

Inhalation: Breathing vapors may cause dizziness, irregular heartbeat, narcosis, nausea, asphyxiation, and anesthetic effects. Product components are a severe irritation to the respiratory tract. Severe overexposure can result in death. May aggravate pre-existing respiratory conditions

Skin Contact: May cause skin irritation. May aggravate pre-existing skin conditions. Solvent components may act as a permeator (absorbed through skin). Long-term exposure may cause defatting of the skin and dermatitis.

Eye Contact: Will cause eye irritation.

Ingestion: Not an expected route of entry. If ingested it may cause irritation to the gastro-intestinal tract.


DANGER! FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. HARMFUL IF INHALED OR SWALLOWED. MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION. USE ONLY WITH ADEQUATE VENTILATION.

HMIS (United States):


HEALTH	2*
FLAMMABILITY	3
REACTIVITY	0
PPE	C

* See Section 11

NFPA (United States):



WHMIS (Canada): B2, D2B



3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	CAS #	% by Weight
Light Hydrotreated Distillate	68410-97-9	30 – 60
Toluene	108-88-3	15 – 30
Methyl Ethyl Ketone	78-93-3	10 – 20

4 FIRST AID MEASURES

Inhalation: Remove patient to fresh air. If patient is having difficulty breathing, seek immediate medical attention. If not breathing, clear airway and start artificial respiration. Seek immediate medical attention. Sudden death due to ventricular fibrillation has been reported in chronic solvent abusers. Overexposure may cause cardiopulmonary failure, CNS depression, peripheral neuropathy, and metabolic acidosis. Treat supportively.

Skin Contact: Remove contaminated clothing. Wash affected areas with soap and water. If irritation develops, seek medical attention.

Eye Contact: Flush eyes with water for 15 minutes. Remove contact lenses prior to water flush. Seek medical attention.

Ingestion: DO NOT induce vomiting. Seek immediate medical attention. DO NOT give anything by mouth to an unconscious person.

5 FIRE FIGHTING MEASURES

Flash Point: 21.0°F (-6.1°C)

Flash Point Method: Closed Cup.

Autoignition Temp.: 399°F (204°C) for lowest known component – Light Hydrotreated Distillate.

Burning Rate: Not Available.

LEL: 0.8% – Light Hydrotreated Distillate.

UEL: 11.5% – Methyl Ethyl Ketone.

Flammability Classification: Class 1B Flammable Liquid

Firefighting Equipment: Use self-contained breathing apparatus (SCBA) with a full-face piece and pressure demand or other positive-pressure mode.

Risk of Explosion Due to Mechanical Impact: Not Available.

Risk of Explosion Due to Static Discharge: Static discharge may serve as an ignition source for this product.

Hazardous Products of Combustion: Carbon Oxides (CO and CO₂) and various Hydrocarbons.

Special Remarks: Flammable liquid and vapor. Vapor may cause flash fires. Vapors are heavier than air and can travel long distances to ignition sources. Highly flammable in the presence of sparks or open flames. Flammable in the presence of heat and/or oxidizing materials. All electrical equipment in the area must be rated for flammable liquids. In case of fire, use dry chemical, CO₂, or alcohol foam. Avoid water. Cool containing vessels with water jet to prevent pressure build-up, autoignition, or explosion.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear appropriate PPE. Flammable liquid and vapor. Remove all sources of ignition. Make sure area is well ventilated. Spilled solvent may be slippery.

Environmental Precautions: Keep out of sewers and drains.

Clean-Up Methods: Dike and contain spill. Absorb spilled product with vermiculite, dry sand, or earth. Place in a suitable non-leaking container and tightly seal for disposal.

7 HANDLING AND STORAGE

Handling Precautions: Wear appropriate PPE. Keep away from heat, sparks, and flames. If used indoors, make sure to provide adequate ventilation to prevent vapor build-up. Bond and ground containers when handling.

Storage Requirements: Store in a cool, dry, well-ventilated area. Ensure product is kept away from all sources of heat, sparks and open flame. Prohibit smoking in the storage area. Do not store with acids or oxidizers. Electrical service in storage area must be rated for flammable liquids.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Provide exhaust ventilation or other engineering controls to keep airborne concentrations of vapors below their respective threshold limit value. Ensure that a working eyewash and safety shower are in the work area.

Protective Equipment: Wear splash goggles or safety glasses with side shields, synthetic apron, and neoprene or rubber gloves. In case of insufficient ventilation, wear an approved (NIOSH) respirator with organic vapor cartridge and dust/mist pre-filter.

Exposure Guidelines / Other:

Product Name	Exposure Limits
Methyl Ethyl Ketone (78-93-3):	OSHA PEL: TWA 200 ppm ACGIH TLV: TWA 200 ppm STEL 200 ppm
Toluene (108-88-3):	OSHA PEL: TWA 200 ppm CL 300 ppm 10 minute max peak 500 ppm ACGIH TLV: TWA 20 ppm

Consult local authorities and local regulations for exposure limits.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear to Light Yellow Liquid.

Physical State: Liquid.

Odor: Strong solvent.

Boiling Point: 174°F (79°C).

Freezing / Melting Point: Not Available.

Molecular Weight: Not Applicable.

Percent Volatile: 79%.

pH: Not Applicable.

Solubility: Not Soluble in Water.

Specific Gravity / Density: 7.0 lbs/gal.

Viscosity: ~ 1200 cP.

Vapor Density: Highest component is 3.14 for Toluene (Air = 1).

Vapor Pressure: 38 mm Hg @ 20°C (calculated).

VOC Calculated (Per Liter of Material): 671 g/L.

10 STABILITY AND REACTIVITY

Stability: Product is stable as supplied.

Conditions to Avoid: All ignition sources and elevated temperatures.

Materials to Avoid (Incompatibility): Strong acids, and alkalis, oxidizing agents, reducing agents, copper, and copper alloys.

Hazardous Decomposition Products: Carbon Oxides (CO and CO₂) and various hydrocarbons.

Hazardous Polymerization: Will not polymerize.

11 TOXICOLOGICAL INFORMATION

Acute Toxicity to Animals:

Methyl Ethyl Ketone (CAS 78-93-3)	Inhalation 4 hour LC50 = 11300 ppm (female rat) Inhalation 4 hour LC50 = 11700 ppm (male rat) Inhalation 4 hour LC50 = 30200 ppm (male mouse) Oral LD50 = 2740 mg/kg (male rat) Oral LD50 = 3140 mg/kg (male mouse) Dermal LD50 > 8050 mg/kg (rabbit)
Toluene (CAS 108-88-3):	Inhalation 4 hour LC50 = 7585 ppm (rat) Inhalation 4 hour LC50 = 7100 ppm (mouse) Oral LD50 = 5580 mg/kg (male rat) Dermal LD50 = 12125 mg/kg (rabbit)

Chronic Toxicity to Animals: No additional information.

Acute Toxicity to Humans: No additional information.

Chronic Effects on Humans: No additional information.

Carcinogenic Effects: Not classifiable for humans or animals.

Mutagenic Effects: Classified NONE for human.

Teratogenic Effects: Classified PROVEN for human (Toluene).

Developmental Toxicity: Classified PROVEN for human (Toluene). Causes damage to kidneys, liver, and central nervous system. Components of this product have been reported to cause spontaneous abortion in women that intentionally concentrated and inhaled vapors.

12 ECOLOGICAL INFORMATION

Ecotoxicity: Product may kill grasses and small plants. Non-toxic to fish. Moderately toxic to amphibians by preventing dermal respiration. May cause gastrointestinal distress to birds and mammals by ingestion.

BOD5 and COD: Not Available.

Biodegradable / OECD: Not Available.

Toxicity of the Products of Biodegradation: Not Available.

Special Remarks on the Products of Biodegradation: Not Available.

13 DISPOSAL CONSIDERATIONS

Spilled, contaminated, or waste material should be put into a suitable container and handled according to Federal, State, and local regulations. Contact a qualified waste management company for assistance. Do not incinerate, weld, cut, or braze container. Residual vapors may be explosive. Empty containers should be disposed of properly.

Dispose of in accordance with Federal, State, and local regulations.

14 TRANSPORT INFORMATION

Proper Shipping Name: Adhesives (DOT), Flammable Liquid.

DOT Classification (1 gallon and 1 quart containers): UN 1133, Adhesives, Flammable Liquid, Hazard Class 3, Packing Group II, Limited Quantity.

DOT Classification (5 gallon & Larger Container): UN 1133, Adhesives, Flammable Liquid, Hazard Class 3, Packing Group II.

Special Provision for Transport: 5 Liters (1.3 gallons) or less may use Limited Quantity Exceptions (49 CFR 172.102 & 49 CFR 173.150).

ADR/RID Classification: Class 3; Flammable Liquid.

ICAO/IATA Classification: Class 3; Flammable Liquid.

IMO/IMDG Classification: Class 3; Flammable Liquid.

Marine Pollutant: No.

15 REGULATORY INFORMATION

U.S. Federal Regulations

Chemical (& CAS Number)	SARA 302 (EHS)TPQ	SARA 304 (EHS)Rq	SARA 313 <i>de minimis</i>	CERCLA Rq	CAA 112(r) TQ	RCRA Code
Toluene (108-88-3)			1	1000		U220

All quantities in pounds

State Regulations

Chemical (& CAS Number)	CA Prop 65	MA RTK	MN RTK	NJ RTK	PA RTK	RI RTK
Methyl Ethyl Ketone (78-93-3)		X	X	X	X	X
Toluene (108-88-3)*	X	X	X	X	X	X

***WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

International Regulations

DSL (Canada): The chemicals in this product are listed.

EINECS: The chemicals in this product are listed.

WHMIS: B2, D2B.

16**OTHER INFORMATION**

Prepared By: Environmental, Health, and Safety Department, Wilsonart LLC.
Telephone: 254-207-7000 Internet: www.wilsonart.com

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named manufacturer nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

END OF MSDS DOCUMENT